



Lexmark MX953se

With the new MX953se monochrome A3 multifunction printer, you get reassuring versatility, exceptional sustainability, and surprising simplicity from such sophisticated technology. Boost your productivity with high-quality prints — up to 55 pages per minute*. Intuitively navigate the 10-inch color touchscreen, and save time with single-pass two-sided scanning.

Print Technology

Monochrome Laser

Function

Color Scanning, Copying, Printing, Trusted Platform Module (TPM), The Trusted Platform Module (TPM) is not available in some countries.

Workgroup Size

Large Workgroup

Touch Screen Display

Yes

Display

Lexmark e-Task 10.1-inch (25.6 cm) color touch screen

Print Speed (Letter, Black)

Up to 55 ppm⁴

Print Speed (Letter, Black) Duplex

Up to 55 spm⁴

Time to First Page (Black)

As fast as 7.3 seconds

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

1200 x 1200 dpi, 2400 IQ

Copy Speed (Letter, Black)

Up to 55 cpm⁴

Copy Speed (Letter, Black) Duplex

Up to 55 spm⁴

Time to First Copy (Black)

As fast as 9.1 seconds

Reduce / Enlarge Range

25 - 400 %

A4/Ltr Simplex Scan Speed (Black)

Up to 100/100 sides per minute

A4/Ltr Simplex Scan Speed (Color)

Up to 100/100 sides per minute

A4/Ltr Duplex Scan Speed (Black)

Up to 200/200 sides per minute

A4/Ltr Duplex Scan Speed (Color)

Up to 200/200 sides per minute

Scan Area, Maximum

11.69 x 17.0 inches

ADF Scan

DADF (single pass Duplex)

Scanner Type

Flatbed scanner with automatic document feeder

Scan Resolution, Enhanced

Up to 600 X 600 dpi

Scan Resolution, Optical

Up to 600 dpi

Scan File Formats (Send as)

JPEG, JPG, PDF, Secure PDF, TIFF, Archival PDF (A-1a, A-1b), Searchable PDF, TXT, RTF, DOCX

Scan Destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer

Processor Speed

Quad Core, 1.2 GHz

Memory, Standard

4 GB

Memory, Maximum

4 GB

Hard Disk

Intelligent Storage Drive included; Magnetic Hard Disk (optional)

Apple Operating Systems Supported

Support is provided through AirPrint and AirScan only

Citrix MetaFrame

Microsoft Windows Server 2012 R2 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Foundation running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 Essentials running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 Standard running Citrix XenApp 6.0, 6.5

Linux Operating Systems Supported

Ubuntu 20.04, Debian 10, SUSE Linux Enterprise Server 12 SP5, OpenSUSE 15.2, Debian 11, Ubuntu 22.04, Fedora 36, Fedora 37, SUSE Linux Enterprise Server 15 SP4, OpenSUSE 15.4, Red Hat Linux 8.7, Red Hat Linux 9.1

Microsoft Windows Operating Systems Supported

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows Server 2012 R2, Windows 10, Windows Server 2016, Windows Server 2019, Windows Server 2022, Windows 11

Novell Operating Systems Supported

Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 2 (SP3) on SuSE Linux Enterprise Server 10 SP4 (x86 and x64) 3, Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64), Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 12 SP1 (x86 and x64), Novell Open Enterprise Server 15 (SP1) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64)

Other Operating Systems Supported

Virtually any platform supporting TCP/IP

Included Paper Handling

550-Sheet Tray, 150-Sheet Multipurpose Feeder, 500-Sheet Output Bin

Optional Paper Handling

550-Sheet Tray, Offset Stacker, 500-Sheet Staple Offset Finisher, 2 x 550-Sheet Tray, 2000-Sheet Tandem Tray, Cabinet, 1,500-Sheet High-Capacity Tray, Paper Transport Unit, Folding Paper Transport Unit, 1,250-Sheet Staple Hole Punch Finisher, 2,250-Sheet Booklet Staple Hole Punch Finisher

Paper Input Capacity, Standard

Up to 700 pages 20 lb or 75 gsm bond

Paper Input Capacity, Maximum

Up to 4750 pages 20 lb or 75 gsm bond

Paper Output Capacity, Standard

Up to 500 pages 20 lb or 75 gsm bond

Paper Output Capacity, Maximum

Up to 2650 pages 20 lb or 75 gsm bond

Paper Weight Range Supported - Standard Tray (lb.)

16 - 80 lb.

Paper Weight Range Supported - Multipurpose Feeder (lb.)

16 - 80 lb.

A3 / 11 x 17

Yes

ADF

200-Sheet Automatic Document Feeder

ADF Paper Input Capacity

Up to 200 pages 20 lb or 75 gsm bond

ADF Paper Output Capacity

Up to 200 pages 20 lb or 75 gsm bond

Finishing Option

Yes

Finishing Functions

Offset stacking, Stapling, Hole punching

Number of Paper Inputs, Standard

2

Number of Paper Inputs, Maximum

6

Media Types Supported

Card Stock, Envelopes, Glossy Paper, Labels, Plain Paper, Vinyl Labels, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A3, A4, A5, B5 Envelope, C4 Envelope, C5 Envelope, DL Envelope, Hagaki Card, Executive, Folio, JIS-B4, JIS-B5, Ledger, Legal, Letter, Statement, Oficio, A6, SRA3, 12 x 18"

Standard Ports

USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), 802.11a/b/g/n/ac + Apple iBeacon

Optional Local Ports

Internal RS-232C serial, Internal 1284-B Bidirectional Parallel

Optional Network Ports

MarkNet N8230 Fiber Ethernet Print Server

Direct USB

Yes

Ethernet Network

Yes

Wireless

Yes

Wireless Network

WPA2™ - Personal, WPA™ and WPA2™ - Personal, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS

Network Protocol Support

TCP, UDP, IPSEC w/ IPv4, IPSEC w/ IPv6, ICMP, IGMP, IPv4, IPv6

Network Printing Methods

Direct IP (Port 9100), Enhanced IP (Port 9400), FTP, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing, Thin Print, LPR

Network Management Protocols

WINS, APIPA (AutoIP), DHCP, DNS, DDNS, mDNS, ARP, BOOTP

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, Certificate Management, SSL Cipher Configuration, TCP/UDP Port Access Control, Security Port Lockdown, TCP Restricted Server List, IPSEC Support (IPv4/IPv6)

Printable Area

0.16 inches of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, PDF 1.7 emulation, PCLm, PCL 5 Emulation

Fonts and Symbol Sets

39 scalable PPDS fonts, 5 PPDS bitmap fonts, 2 PCL 5/6 bitmap fonts, 163 scalable PostScript fonts, 94 scalable PCL 5/6 fonts

Laser Cartridge Yields (up to)³

. 47,700-page Black Cartridge

Imaging Unit Estimated Yield

Up to 225,000 pages, based on 5 average letter/A4 size pages per print job and ~ 5% coverage for CS/CX96x, CX83x, CX95x, and MX95x printer series, or based on 3 average letter/A4 size pages per print job and ~ 5% coverage for all other printers

Cartridge(s) Shipping with Product

5,000-page Black Toner Cartridge

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/ regions for more details.

Packaged Size (in. - H x W x D)

42.5 x 29.1 x 30.9 in.

Packaged Weight (lb.)

206.8 lb.

Size (in. - H x W x D)

31.9 x 23.3 x 26.0 in.

Weight (lb.)

162.5 lb.

Noise Level, Idle

14 dBA

Noise Level (Print), Operating

51 dBA

Duplex Print Noise Level, Operating

52 dBA

Noise Level (Copy), Operating

53 dBA

Noise Level (Scan), Operating

42 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.2 watts

Average Power (Sleep Mode)

1 watts

Average Power (Ready Mode)

61 watts

Average Power (Printing)

756 watts

ENERGY STAR Typical Electricity Consumption (TEC)

0.8 kilowatt-hours per week

Product Certifications

ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, UL, cUL, FDA/CDRH, IEC 60825-1, CB Certified, ISO-532B, CE (EU) DoC, RCM DoC, UKCA DoC, Blue Angel DE-UZ 219, UL-AR, GS Mark, ISO-9296, Mopria Certified®, EPEAT Gold

Maximum Monthly Duty Cycle

Up to 270 000 pages per month²

Recommended Monthly Page Volume

7000 - 50000 pages¹

Specified Operating Environment

Humidity: 15 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet), Temperature: 10 to 32.2°C (50 to 90°F)

Country of Origin

North America & TAA Compliant - Mexico, Rest of World - PRC

UNSPSC Code

43212110

Harmonized Tariff Code

8443.31.0000

¹Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device

performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

²"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

³Average standard page yield value declared in accordance with ISO/IEC 19752.

⁴Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.



| Callout | Availability | Description |
|---------|--------------|--|
| 1 | Standard | |
| 10 | Optional | Paper Transport Unit |
| 11 | Optional | Folding Paper Transport Unit |
| 12 | Optional | 500-Sheet Staple Finisher |
| 13 | Optional | Offset Stacker |
| 14 | Optional | 1,250-Sheet Staple Hole Punch Finisher |
| 15 | Optional | 2,250-Sheet Booklet Staple Hole Punch Finisher |
| 2 | Standard | 500-Sheet Output Bin |
| 3 | Standard | 150-Sheet Multipurpose Feeder |
| 4 | Standard | 550-Sheet Tray |
| 5 | Optional | |
| 6 | Optional | 2 x 550-Sheet Tray |
| 7 | Optional | 2,000-Sheet Tandem Tray |
| 8 | Optional | Cabinet |
| 9 | Optional | 1,500-Sheet High-Capacity Tray |