

Xerox® WorkCentre® EC7836/EC7856 Color Multifunction Printer

WorkCentre EC7836/EC7856 Color Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.



System Specifications	WorkCentre EC7836	WorkCentre EC7856
Speed Color / Black and White	Up to 35 / 35 ppm	Up to 50 / 55 ppm
Monthly Duty Cycle¹	Up to 110,000 pages / month ¹	Up to 300,000 pages / month ¹
Recommended Average Monthly Print Volume²	10,000 to 15,000 pages	18,000 to 22,000 pages
Hard Drive / Processor / Memory	Up to 250 GB HDD / 1.2 GHz Dual-core / 2 GB system plus 1 GB page memory	
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print, Wi-Fi Direct with Optional Xerox® USB Wireless Adapter	
Controller Features	Unified Address Book, Remote Control Panel, Online Support (accessed from the user interface and print driver), Configuration Cloning	
Device Specifications		
Control Panel Languages	US English, Canadian French, Spanish (Mexico), Brazilian Portuguese	
Accessories		
Optional	High Capacity Feeder (HCF) Office Finisher LX Booklet Maker for Office Finisher LX Hole Punch for Office Finisher LX Convenience Stapler (includes Work Surface) Smart Card Enablement Kit Walk up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi Direct with Optional Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit XPS Print Option Kit	

Xerox® WorkCentre® EC7836/EC7856 Color Multifunction Printer

Xerox® Adaptable Accessibility Solution	This assistive, Section 508-compliant technology provides an alternative to the existing user interface on the multifunction printer, enabling wheelchair users and those who are blind or visually impaired to easily release their Secure Print jobs. These are jobs submitted with a PIN, that are held at the printer. Users can also easily program jobs for email, scanning and faxing. The Android™ tablet is attached to a rotatable bracket, giving wheelchair users easy, viewable accessibility. For the blind and visually impaired, a talkback feature is included, as well as increased magnification of the UI. In addition, the USB keyboard (included in the kit) is integrated with Common Access Card (CAC) solutions.			
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access Device, this is an interface to third party access control devices, such as coin machines and card readers.			
Electrical Requirements				
North America	Voltage: 110-127 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 %, 15 A			
Power Consumption	WorkCentre EC7836		WorkCentre EC7856	
Running (Average)	673 watts		828 watts	
Standby Mode	62 watts		85.7 watts	
Low Power Mode	59 watts		80 watts	
Auto Off / Sleep mode	4.2 watts (Default time to Sleep mode = 2 mins)		4.3 watts (Default time to Sleep mode = 2 mins)	
Operating Environment				
Required Temperature Range	50° to 82° F (10° to 28° C)			
Required Relative Humidity	15 % to 85 %			
Sound Power Levels Operating Standby	6.5 LwAd (B) 3.4 LwAd (B)		6.8 LwAd (B) 3.6 LwAd (B)	
Sound Pressure Levels Operating Standby	54.3 LpAd (dBA) 16.5 LpAd (dBA)		55.8 LpAd (dBA) 18.5 LpAd (dBA)	
Boot Time (from Off to UI Ready)	WorkCentre EC7835: As fast as 157 seconds WorkCentre EC7856: As fast as 151 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 9 seconds			
Dimensions and Weight	Width	Depth	Height	Weight
Base Unit	41.9 in. / 1,064 mm	27.5 in. / 699 mm	45.2 in. / 1,149.2 mm	321 lbs. / 146 kg
With Office Finisher LX (with Booklet Maker)	65.6 in. / 1,666 mm	27.9 in. / 709 mm	45.2 in. / 1,149 mm	403 lbs. / 183 kg

Xerox® WorkCentre® EC7836/EC7856 Color Multifunction Printer

Certifications		
	FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition) NOM Mopria® Certified Wi-Fi Direct Certification ECOLOGO® Common Criteria (IEEE 2600.2 standard) (undergoing evaluation) Citrix® Certified WHQL IPv6 Ready Cerner MEDITECH SAP To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .	
Print		
First-print-out Time	As fast as 9 seconds color	As fast as 7.1 seconds color
	As fast as 7.7 seconds black	As fast as 5.9 seconds black
Print Resolution	Up to 1200 x 2400 dpi	
Page Description Languages	Adobe® PostScript® 3™ Adobe® PDF version 1.7 PCL® 5c / PCL 6 XML Paper Specification (XPS®) (Optional)	
Print Features	Application Defaults Banner Sheet Enable / Disable Bi-directional Real-time Status Custom Color Options (Color By Words) Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, Enhanced, High)) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout / Watermark N-up (up to 16 pages per sheet) Booklet layout Finishing Fit to new paper size Hold All Jobs Paper Selection by Attribute LAN Fax (requires optional Fax Kit) Sample Set Saved Job (color jobs can be printed as monochrome) Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default)	
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS4, PCL Color jobs can be printed as monochrome	

Xerox® WorkCentre® EC7836/EC7856 Color Multifunction Printer

Operating Systems	Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 (64-bit) Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Mac OS 10.8, 10.9, 10.10, 10.11 Linux® Redhat® Fedora® Core 20 x86 Ubuntu® 14.04 x64 openSUSE® 13.1 x64	
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Copy	WorkCentre EC7836	WorkCentre EC7856
Document Scanner	110-sheet Duplex Automatic Document Feeder	130-sheet Single-pass Duplex Automatic Document Feeder
First-copy-out Time (Letter/A4-size, from Platen to Center Tray)	As fast as 8.2 seconds color	As fast as 7.1 seconds color
	As fast as 6.8 seconds black	As fast as 5.5 seconds black
Sides (input:output)	1:1, 1:2, 2:2 and 2:1	
Quantity	1 to 999	
Resolution (max.)	Up to 600 x 600 dpi	
Reduction / Enlargement	Variable zoom from 25 % to 400 % in 1 % increments	
Concurrency	Program-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)	
Copy Features	Annotation and Bates™ stamping (with color capability and font size adjustment) Authentication for Services (i.e. Color Copy) Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Color Stapling Transparencies	
Xerox® Copier Assistant® Software	Xerox® Copier Assistant Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508-compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com .	

Xerox® WorkCentre® EC7836/EC7856 Color Multifunction Printer

Scan	WorkCentre EC7836	WorkCentre EC7856
Capability	Black and white and color scanning	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)	
Input Speed	Scan at up to 70 ipm color scanning, up to 70 ipm black-and-white – 8.5 x 11 in. / A4 LEF	Scan at up to 133 ipm color scanning, up to 133 ipm black-and-white – 8.5 x 11 in. / A4 LEF
Resolution	72 x 72 dpi to 600 x 600 dpi	
Bit Depth	1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)	
Maximum Scan Area	11 x 17 in. / A3	
Network Filing Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS	
File Compression	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) Linearized PDF / PDF/A	
File Formats	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF Encrypted / Password-protected PDF Linearized PDF and PDF/A	
Supported Scan Destinations	Scan to Mailbox Scan to USB Scan to Email Scan to Network Scan to Home	
Scan Template Management	Supports 250 scan templates Create Xerox® CentreWare® Internet Services scan templates and share via device cloning to other MFPs Confirmation sheet options	
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customized fields viewed on user interface for variable data input 	
Scan Features	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA 2.0 Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)	
Unified Address Book for Fax, Internet Fax, Email and Scan to...		
	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of all services supported	

Xerox® WorkCentre® EC7836/EC7856 Color Multifunction Printer

Scan to Email (Standard)	
Scan Features	<ul style="list-style-type: none"> • Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options • Scan to Email S/MIME Encryption • Email Signing (requires Smart Card option) • Auto send to self
Directory Access	Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format) Utilizes the Unified Address Book
Scan to... (Standard)	
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)
Network Scanning – Software Solutions	
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled multifunction printer.
Fax	
Network Server Fax Features	
Compatibility	ITU (CCITT) group 3 Various Xerox Business Innovation Partner Solutions
Maximum Scan Area	11 x 17 in. / A3
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in. / A3) Add to Send List (50 numbers maximum) Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi
Internet Fax Features	
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients
Directory Access	Utilizes the Unified Address Book
Send / Receive	Multi-page TIFF, Image only PDF
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)
Network Protocols	SMTP (send), POP3 (receive)
Compliance	ITU-T T.37 compliant
Walk-up Fax Features (Optional (Customer-installable) – 1 and 2 lines)	
Compatibility	ITU (CCITT) Group 3
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilizing T38 (optional)
Compression / Speed	MH/G3, MMR/SG3

Xerox® WorkCentre® EC7836/EC7856 Color Multifunction Printer

Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report
Directory Access	Utilizes the Unified Address Book Group fax available
Auto Redial	Up to 14 attempts (per country requirements) • 1 to 25 minute intervals
Auto Resend	Up to 5 attempts
Mobile Solutions and Mobile Device Apps	
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. Our Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.

Xerox® WorkCentre® EC7836/EC7856 Color Multifunction Printer

Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	<p>The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.</p>
Xerox® Mobile Link App (Free at Google Play™ Store and Apple® App Store)	<p>The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer.</p>
Xerox® Print Management and Mobility Suite, Xerox® Print Management and Mobility Service	<p>Xerox® Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.</p>
Security	
Standard Security Features	<ul style="list-style-type: none"> • Expanded Authentication <ul style="list-style-type: none"> – Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2008), SMB (Windows Server 2008), NDS, LDAP authentication – Local Authentication (internal database) – Smart Card authentication -144k CAC / PIV Card Support (2048-bit certificate key) /.NET • Secure Data <ul style="list-style-type: none"> – Digitally signed PDF (when using Smart Card authentication) – Encrypted Scan to Email – Encrypted Password Protected PDF (when using Email and Network Scan Templates only) – Secure Print (up to 10-digit PIN or Network Authentication) – Immediate Image Overwrite / Securely delete jobs using approved algorithms – On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk – FIPS 140-2 – 256-bit Hard Disk Encryption • Expanded Authorization <ul style="list-style-type: none"> – SA access based on network credentials – Authorization per user per service – User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver • Secure Network Access • IP Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPs, 802.1X, Device Security <ul style="list-style-type: none"> – McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) • Common Criteria Certification ISO 15408 (undergoing evaluation)
Accounting	
Xerox® Standard Accounting Tool / Network Accounting (Standard)	
Tracking	<p>Copy, Print, Fax, Scan and Email usage</p>
Accounting	<p>Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)</p>
Features	<ul style="list-style-type: none"> • Administrator can manage the feature via the Web User Interface or device control panel in tools • Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file

Xerox® WorkCentre® EC7836/EC7856 Color Multifunction Printer

Accounting Options – Network Accounting (Allows central server to manage all accounting)		
	<ul style="list-style-type: none"> Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support <ul style="list-style-type: none"> Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface 	
Paper Handling	WorkCentre EC7836	WorkCentre EC7856
Document Feeder		
Capacity ³	Duplex Automatic Document Feeder: 110 sheets	Single-pass Duplex Automatic Document Feeder: 130 sheets
Speed	up to 70 image per minute black and white and color (simplex)	up to 80 images per minute black and white and color (simplex) / up to 133 images per minute black and white and color (duplex)
Paper Sizes Sensed	5.5 x 8.5 in. to 11 x 17 in. / A5 to A3	
Weights	16 lb. bond to 32 lb. bond / 60 to 128 gsm	
Bypass Tray		
Capacity ³	100 sheets	
Sizes	Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in. / 89 x 98 mm to 320 x 483 mm	
Weights	16 lb. bond to 110 lb. cover / 60 to 280 gsm	
Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain Reloaded Preprinted Recycled Transparencies	
High Capacity Tandem Tray		
Capacity ³	Tray 1: 520 sheets Tray 2: 520 sheets Tray 3: 867 sheets Tray 4: 1,133 sheets	

Xerox® WorkCentre® EC7836/EC7856 Color Multifunction Printer

Sizes	Tray 1: Custom Sizes from 5.5 x 7.2 in. SEF to 11.7 x 17 in. SEF / 140 x 182 mm to 297 x 432 mm Tray 2: Custom Sizes from 5.5 x 7.2 in. SEF to 12.6 x 18 in. SEF / 140 x 182 mm to 320 x 457.2 mm Trays 3-4: Standard Sizes: 8.5 x 11 in. LEF / A4, JIS B5, Executive (7.25 x 10.5 in.)
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm
Types	Bond Card Stock Custom Glossy Card Stock Hole punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted
High Capacity Feeder (HCF) (Optional)	
Capacity³	2,000 sheets
Sizes	Standard Sizes: 8.5 x 11 in. / A4 LEF
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm
Total Capacity	
Device Total Capacity³	5,140 sheets
Finishing	
Output Trays (Standard)	
Stacking Trays³	Dual Offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheets
Office Finisher LX (Optional)	
Capacity³	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)
Sizes	8.3 x 7.2 in. to 11.7 x 17 in. / 210 x 182 mm to 297 x 432 mm
Weights	16 lb. bond to 80 lb. cover / 60 to 256 gsm
Multiposition Stapling	50 sheets of 24 lb. bond / 90 gsm
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch
Booklet Maker for Office Finisher LX (Score/Crease, Saddle-stitch Staple) (Optional)	
Capacity³	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)
Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm
Score / Crease	1-15 sheets / unstapled
Convenience Stapler and Work Surface (Optional)	
Capacity³	50-sheet stapling 5,000 staples Requires a separate outlet

Xerox® WorkCentre® EC7836/EC7856 Color Multifunction Printer

Device Management	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP IPv6 Secure FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
Novell NDPS/NEPS	Server gateway application: centralized management tool
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: <ul style="list-style-type: none"> • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities
Xerox Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions
Xerox Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox Font Center Barcode Fonts. Information available at www.office.xerox.com/software-solutions
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions
Xerox® CentreWare® Web	
	<ul style="list-style-type: none"> • A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
Xerox® CentreWare Internet Services – Integrated Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts Remote Control Panel
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS ⁴ , TXT, PRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device

Xerox® WorkCentre® EC7836/EC7856 Color Multifunction Printer

Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese, Arabic
Remote Services	
Xerox® Meter Assistant® Service	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® Supplies Assistant® Service	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.

Xerox® WorkCentre® EC7836/EC7856 Color Multifunction Printer

Supplies and Accessories	Quantity	Part Number
Supplies		
Toner Cartridges (Metered)	Black: 26,000 standard pages ⁵ Cyan: 15,000 standard pages ⁵ Magenta: 15,000 standard pages ⁵ Yellow: 15,000 standard pages ⁵	006R01509 006R01512 006R01511 006R01510
Toner Cartridges (Sold)	Black: 26,000 standard pages ⁵ Cyan: 15,000 standard pages ⁵ Magenta: 15,000 standard pages ⁵ Yellow: 15,000 standard pages ⁵	006R01513 006R01516 006R01515 006R01514
Transfer Belt Cleaner	1 Assembly: 160,000 standard pages	001R00613
Second Bias Transfer Roll	1 Assembly: 200,000 standard pages	008R13064
Staple Cartridges	Office Finisher LX and Convenience Stapler (1 cartridge per carton): 5,000 each cartridge	008R12964
	Office Finisher LX Booklet Maker (8 cartridges per carton): 2,000 each cartridge	008R12897
Staple Refills	Office Finisher LX and Convenience Stapler (3 refills per carton): 5,000 each refill	008R12941
Xerox® Smart Kit® Technology		
Drum Cartridge	1 Cartridge per Color: 125,000 pages ⁶	013R00662
Waste Toner Container	1 Cartridge: 43,000 pages ⁷	008R13061

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ XPS option is required to print XPS files.

⁵ Assumptions: Toner cartridge yield is based on 5 % area coverage on 8.5 x 11 in. / A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality setpoints.

⁶ Average drum yield is based on a run length of 5 pages of 8.5 x 11 in. / A4 LEF pages, with split of 30 % color / 70 % black-and-white pages.

⁷ Waste Toner Container yield will vary depending on type of image, area coverage % and Job run length.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office

Configurations vary by geography.